

# C26 Series

410A



# Applied COMFORT

INDUSTRY STANDARD SLEEVE

## 16 x 26"

ROOM AIR CONDITIONERS ---- TTW

COOLING ONLY | COOLING + ELECTRIC HEAT

## Applied Comfort™ C26 Series Built-in Air Conditioners.

Direct fit replacement for many models, so all you have to do is take out the old unit and slip in the Applied Comfort Built-In Air Conditioner. It installs in most major sleeves without additional cost of adapter kits or wall remodelling.

High energy efficiency with models up to 9.8 EER saving you energy costs compared to the units you are replacing.

Installs weathertight in most common 16 x 26" sleeves with the use of trim kit.

Premium Components provide exceptional reliability, durability, low sound, and long-life.

Warranty by Applied Comfort Products.

Available as Reverse-Cycle Heatpumps with Backup Heat

Contact Applied Comfort for more information and to discuss availability of other models.



Loaded with Features.

26"(W) X 15-5/8"(H) X 16-7/8"(D)  
 Four fan speeds: Auto/Lo/Med/Hi  
 Electronic touch pad thermostat  
 Hand held controller  
 Slide-out chassis

Fan cycle switch  
 4-way adjustable air discharge  
 Hidden vent control  
 Easy to clean filter

Model	C26ED09L00	C26ED12L00	C26ED09K00	C26ED12K00	C26EC09K35	C26ED12K25
Function	COOLING	COOLING	COOLING	COOLING	COOLING + ELECTRIC HEAT	COOLING + ELECTRIC HEAT
Rated Voltage	115V	115V	230/208V	230/208V	230/208V	230/208V
Rated Frequency	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz
Maximum Overcurrent Protection (A)	15	15	15	15	20	20
Cooling Capacity (Btu/h)	9200	11800	9200/8900	11800/11400	9200/8900	11800/11400
Heating Capacity (Btu/h)					11000/9000	11000/9000
Power Input Cooling (W)	940	1260	940/910	1200/1160	940/910	1200/1160
Power Input Heating (W)					3500/2900	3500/2900
EER	9.8	9.4	9.8	9.4	9.8	9.4
Fan Motor Speed (rpm) (H/M/L)	1070/1000/920	1070/1000/920	1070/1000/920	1070/1000/920	1070/1000/920	1070/1000/920
Dimension (W/H/D)( mm)	660/397/429	660/397/429	660/397/429	660/397/429	660/397/429	660/397/429
Dimension of Package (L/W/H)( mm)	753/620/460	753/620/460	753/620/460	753/620/460	753/620/460	753/620/460
Net Weight /Gross Weight (lbs)	86/101	86/101	86/101	86/101	86/101	86/101
Refrigerant Charge (kg)	R410a/0.6	R410a/0.63	R410a/0.59	R410a/0.63	R410a/0.59	R410a/0.63

Specifications subject to change without notice.

### Accessories.

- 16 x 26" Stamped Grille - durable light-weight aluminum  
ACC26SAGRILLE ACC26SAGRILLE-CUSTOM
- 16 x 26" Wall Sleeve - powder-coated galvanized steel  
ACC26SLEEVE-FULL
- 16 x 27" Expansion Frame - powder-coated galvanized steel to fit Fedders 16 x 27" sleeve.  
ACC26FRAME27

Distributed By:

Applied Comfort Products Carver Inc.  
 TRUSTED MANUFACTURER OF HIGH QUALITY PTACS