

# C26 Series

410A



INDUSTRY STANDARD SLEEVE

## 16 x 26"

Thru-The-Wall ROOM AIR CONDITIONERS

COOLING  
ONLY

COOLING  
+ ELECTRIC HEAT

HEATPUMP  
+ ELECTRIC HEAT

## Applied Comfort™ C26 Series Built-in Air Conditioners.



Loaded with Features.

26"(W) X 15-5/8"(H) X 16-7/8"(D)  
Electronic touch pad thermostat  
Hand held controller (optional)  
Slide-out chassis  
Efficient rotary compressor

Fan cycle switch  
4-way adjustable air discharge  
Hidden vent control  
Energy saver mode  
Easy to clean filter

Direct fit replacement for GE and Amana 26" wide TTW models. Installs weathertight in most common 16 x 26" sleeves with the use of trim kit.

High energy efficiency with models up to 11.7 EER, saving you energy costs compared to the units you are replacing.

26" Trim Kit available for Friedrich and Fedders wall sleeves (Fedders #BSA00C and Friedrich #WSC)

Premium Components provide exceptional reliability, durability, low sound, and long-life.

Warranty by Applied Comfort Products Carver Inc.

C26 products are covered by a standard 1 year comprehensive parts & labor warranty, and a 6 year compressor parts warranty.

|                                   | Cooling Only Models |                 |                 |                 | Electric Heat Models |                 | Heat Pump Models |                 |                 |
|-----------------------------------|---------------------|-----------------|-----------------|-----------------|----------------------|-----------------|------------------|-----------------|-----------------|
|                                   | C26EC09L00E6        | C26EC12L00E6    | C26EC09K00E6    | C26EC12K00E6    | C26EC09K34E7         | C26EC12K34E7    | C26HC09L12E6     | C26HC09K34E7    | C26HC12K34E7    |
| <b>Voltate</b>                    | 115                 | 115             | 230 / 208       | 230 / 208       | 230 / 208            | 230 / 208       | 115              | 230 / 208       | 230 / 208       |
| <b>NEMA plug configuration</b>    | 5-15P               | 5-15P           | 6-15P           | 6-15P           | 6-20P                | 6-20P           | 5-15P            | 6-20P           | 6-20P           |
| <b>Airflow CFM</b>                | 283 / 247 / 188     | 283 / 247 / 188 | 270 / 235 / 177 | 270 / 235 / 177 | 270 / 235 / 177      | 270 / 235 / 177 | 283 / 247 / 188  | 270 / 235 / 177 | 270 / 235 / 177 |
| <b>Net Wt / Ship Wt lb</b>        | 97 / 110            | 97 / 110        | 97 / 110        | 97 / 110        | 97 / 110             | 97 / 110        | 97 / 110         | 97 / 110        | 97 / 110        |
| <b>Temperature limiting</b>       | Yes                 | Yes             | Yes             | Yes             | Yes                  | Yes             | Yes              | Yes             | Yes             |
| <b>Check filter indicator</b>     | Yes                 | Yes             | Yes             | Yes             | Yes                  | Yes             | Yes              | Yes             | Yes             |
| <b>(Optional) handheld contr</b>  | Yes                 | Yes             | Yes             | Yes             | Yes                  | Yes             | Yes              | Yes             | Yes             |
| <b>Cooling:</b>                   |                     |                 |                 |                 |                      |                 |                  |                 |                 |
| <b>BTUH</b>                       | 9000                | 11800           | 9400 / 9300     | 11800 / 11600   | 9400 / 9300          | 11800 / 11600   | 9000             | 9300 / 9100     | 11700 / 11500   |
| <b>Watts</b>                      | 920                 | 1200            | 940 / 910       | 1185 / 1145     | 940 / 910            | 1185 / 1145     | 920              | 940 / 910       | 1220 / 1200     |
| <b>EER</b>                        | 9.8                 | 10.6            | 10.0 / 10.2     | 10.0 / 10.1     | 10.0 / 10.2          | 10.0 / 10.1     | 9.8              | 9.9 / 10.0      | 9.6 / 9.6       |
| <b>Electric Heat:</b>             |                     |                 |                 |                 |                      |                 |                  |                 |                 |
| <b>Watts</b>                      | /                   | /               | /               | /               | 230V - 3.4           | 230V - 3.4      | 115V - 1.2       | 230V - 3.4      | 230V - 3.4      |
| <b>Heat Pump (reverse cycle):</b> |                     |                 |                 |                 |                      |                 |                  |                 |                 |
| <b>BTUH</b>                       | /                   | /               | /               | /               | /                    | /               | 8500             | 8800 / 8600     | 11400 / 11200   |
| <b>Watts</b>                      | /                   | /               | /               | /               | /                    | /               | 805              | 830 / 810       | 1160 / 1140     |
| <b>C.O.P.</b>                     | /                   | /               | /               | /               | /                    | /               | 3.1              | 3.1 / 3.1       | 2.9 / 2.9       |

### Accessories.

|   |                  |
|---|------------------|
| 16 x 26" Architectural Grille - aluminum              | ACC26AAGRILLE    |
| 16 x 26" Wall Sleeve - powder-coated galvanized steel | ACC26SLEEVE-FULL |
| 16 x 27" Fedder/Friedrich Sleeve Trim Kit             | ACC26FRAME27     |

Applied Comfort Products Carver Inc.  
TRUSTED MANUFACTURER OF HIGH QUALITY PTACS

Distributed By:

