

WallMate

UNIVERSAL REPLACEMENT
FOR:

Electrohome™ AW905

Carrier™ 51KZ

Beaumarck™ 77905

Sears Kenmore™ C938

Applied Comfort™ SC

Friedrick™ USC / WSC

Whirlpool™ / Fedders™ 26³/₄" x 15³/₄"

Frigidaire™ 25⁷/₈" x 15⁷/₁₆"

GE™ / Amana™ / Sanyo™ 26 x 15⁵/₈"



Applied
COMFORT

Applied Comfort™ WallMate Built-in Air Conditioners.

Complete comfort with easy to use controls.

Direct fit replacement for many models, so all you have to do is take out the old unit and slip in the Applied Comfort Built-In Air Conditioner. It installs in most major sleeves without additional cost of adapter kits or wall remodelling.

High energy efficiency with models up to 9.6 CEER saving you energy costs compared to the units you are replacing.

Installs weathertight in most common sleeves with the use of optional trim kit.



Model Number	WMC09L00S
Cooling Capacity (BTU/HR)	9300
Standby Power WATTS	0
On Move Power WATTS	970
CEER	9.6
Fan Motor Speeds	3
Wiring Receptacle	115v - 15A
Refrigerant	R410a
Chassis Cabinet Height	14 1/2" (36.9 cm)
Chassis Cabinet Width	22 1/4" (56.5 cm)
Chassis Cabinet Depth	20 7/8" (53 cm)
Smallest Sleeve Dimensions	23" (58.4 cm) W x 15 9/32" (38.8 cm) H
Appx. Net Weight	90 lbs (40.8 kg)
Appx. Ship Weight	93 lbs (42 kg)

Specifications Subject to Change Without Notice

All brands and product names are trademarks or registered trademarks of their respective owners.

Universal Replacement for:	Sleeve Dimension	
	Width In.	Height In.
Electrohome / Applied Comfort / Keeprite / RCA / Admiral / Beaumarck	23	15 9/32
Westinghouse	24 1/2	14 1/2
Carrier	24 5/16	15 3/4
GE	25 1/4	14 5/8
Frigidaire	25 7/8	15 7/16
Friedrich USC	25 7/8	15 17/32
26" GE / Amana / Sanyo ST	26	15 5/8
Friedrich	26 5/8	16 11/16
Whirlpool / Friedrich WSC / Fedders	26 3/4	15 3/4

Easy to access, easy to remove, easy to clean polypropylene filter; no tools required.

100% FULL factory run tests are performed on all units to ensure high reliability and dependability.

4-Way adjustable airflow to direct cool comfort to any area of a room.

3-cooling speeds and 3 fan-only speeds to enhance comfort.



* 1ST YEAR PARTS AND LABOR
2ND TO 6TH YEAR COMPRESSOR PARTS
FREE PARTS SHIPPING
OPTIONAL 6 YEAR COMPRESSOR LABOR



EFFICIENT

www.ptacs.com

RELIABLE

WallMate

REPLACEMENT IDEAL
POUR:

Electrohome™ AW905

Carrier™ 51KZ

Beaumarck™ 77905

Sears Kenmore™ C938

Applied Comfort™ SC

Friedrich™ USC / WSC

Whirlpool™ / Fedders™ 26³/₄" x 15³/₄"

Frigidaire™ 25⁷/₈" x 15⁷/₁₆"

GE™ / Amana™ / Sanyo™ 26 x 15⁵/₈"



Applied
COMFORT

Climatiseur encastré WallMate d'Applied Comfort™.

Un confort inégalé avec contrôles faciles à utiliser.

Remplacement idéal pour plusieurs modèles. Vous n'avez qu'à retirer le vieil appareil et y glisser votre WallMate. S'insère dans la majorité des manchons existants sans besoin de restructurer vos murs.

Moins énergivore que les anciens appareils, son rendement d'efficacité énergétique peut atteindre 9.6.

Adaptation adéquate et esthétique à la plupart des manchons existants à l'aide du cadre contour (vendu séparément).



Model	WMC09L00S
Refroidissement (BTU/HR)	9300
Standby Power WATTS	0
Refroidissement WATTS	970
REE	9.6
Vitesse de ventilation	3
Prise	115v - 15A
Refrigerant	R410a
Hauter du boitier	14 1/2" (36.9 cm)
Largeur du boitier	22 1/4" (56.5 cm)
Profondeur du boitier	20 7/8" (53 cm)
Manchon moral	23" (58.4 cm) W x 15 9/32" (38.8 cm) H
Poids net.	90 lbs (40.8 kg)
Pods net de transport	93 lbs (42 kg)

Remplacement pour:	Conçu pour manchon	
	Largeur po.	Hauteur po.
Electrohome / Applied Comfort / Keeprite / RCA / Admiral / Beaumarck	23	15 9/32
Westinghouse	24 1/2	14 1/2
Carrier	24 5/16	15 3/4
GE	25 1/4	14 5/8
Frigidaire	25 7/8	15 7/16
Friedrich USC	25 7/8	15 17/32
26" GE / Amana / Sanyo ST	26	15 5/8
Friedrich	26 5/8	16 11/16
Whirlpool / Friedrich WSC / Fedders	26 3/4	15 3/4

Filtere facile à enlever pour un nettoyage rapide, aucun outil requis.

100% de nos climatiseurs sont testés en usine afin d'assurer la fiabilité.

Déflexeur d'air ajustable à 4 positions afin de diriger l'air dans les endroits désirés.

Moteur à 3 vitesses pour la climatisation ou la ventilation seulement.

VÉRIFIÉ POUR
PERFORMANCES
ÉNERGÉTIQUES



6 YEAR
WARRANTY*



* 1ST YEAR PARTS AND LABOR
2ND TO 6TH YEAR COMPRESSOR PARTS
FREE PARTS SHIPPING
OPTIONAL 6 YEAR COMPRESSOR LABOR

Les données techniques peuvent être modifiées sans préavis. Toutes les marques et noms de produits sont des marques de commerce ou des marques déposées de leurs propriétaires respectifs.

EFFICACE

www.ptacs.com

FIABLE